

# OTDR-3600

10-in-1 Touch Screen OTDR



## TECHNICAL SPECIFICATIONS

Model	OTDR-3600
Wavelength	1310/1550nm
Dynamic range	32/30dB
Distance setting	Max. 150km
Connector	SC/UPC interchangeable adapter or customized
Pulse width	5ns~20μs
Event dead zone	1m
Attenuation dead zone	6m
OLS function	Same wavelength and connector as OTDR
OPM function	+26~-50dBm, 850/1300/1310/1490/1550/1625nm, 2.5mm UPP
VFL function	10mW, 2.5mm universal connector
Storage	Internal memory or TF card(optional)
Power & Data port	TYPE-C USB
Power bank	Type-A 3.7V, 5000mAh
Operation Temperature	0~+50°C, <90% RH
Storage Temperature	-20~+70°C, <90% RH
Size	160*85*38mm
Weight	About 430g

## ACCESSORIES

### STANDARD



Carrying Bag



Manual



Calibration Certificate



AC/DC Adapter  
Type -C

### OPTIONAL ACCESSORIES



FCU=FC/UPC  
FCA=FC/APC



SCU=SC/UPC  
SCA=SC/APC



SCU male-SCA female



LCU=LC/UPC



STU=ST/UPC



SCA male-SCU female

## ORDERING INFORMATION

OTDR-3600, 1310/1550nm, 32/30dB, OTDR SC/UPC connector